TIGER GRIP ENGINEERING

TECHNICAL SHEET

Edit in : January 2020

EASY-GRIP WHITE

Anti-slip overshoe



REF « EGB »

- Composition: 100% rubber.
- Professional use: For greasy, wet and slipping surfaces.

Outstanding grip coefficient
Stretch fit structure : 4 Sizes from 34 to 50
Color-coded sizes : identify the size at a single glance
Can be adapted to most kind of footwear
Hygienic and comfortable solution
Reusable and waterproof
Tiger-grip ® antislip sole with self cleaning studs

Certifications

PPE REGULATION (EU) : 2016/425
(personal protective equipment)

EUROPEAN STANDARDS

CE certification : 0075/1344/161/07/13/0626

- NF EN ISO 20347 /2012
- NF EN 13287
- Oil resistance (FO)

CE PPE CERTIFIED Risk II

Certified organism:
CTC N° 0075/69367 Lyon - France

AMERICAN STANDARDS

- ASTM F 2913

CANADIAN STANDARDS

- Acceptance EN ISO 13287 (SRC)

- **NF EN 13287 – Antislip properties**

Certification SRC = SRA + SRB

SRB : Anti-slip coefficient on steel floors with glycerin

SRA: Anti-slip coefficient on ceramic floors with detergent

Surface	Contact with	Standard ISO 13287	EASY-GRIP results
Steel	Oil	SRB = 0.18	+ 340% = 0.62
Ceramic	Detergent	SRA = 0.32	Up to +140% = 0.54
	Water	-	0.62

Physico-mechanical test

Test	Hardness	Abrasion resistance	Density	Breaking traction resistance	Breaking extension	Tearing resistance
Standard		ISO 4649/2002	ISO 4649/2002	EN 12803	EN 12803	ISO 34-1- Méth. A
Unit	Shore A	Mm^3	g/cm^3	daN/cm^2	%	daN/cm
EASY-GRIP results	50	140	1,16	137	603	10,5

Antistatism: *The overshoe meets antistatic properties.*
The shoe and overshoe combination must necessarily be tested by the user

Sizes



	S				M				L				XL		
EU Sizes	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48 +
UK Sizes	1	2	3	4	5	6	6,5	7	8	9	10	10,5	11	12	13 +
US Woman	4	5	6	7	7,5	8	8,5	9,5	10	11					
US Man					5,5	6	7	8	8,5	9,5	10	11	11,5	12,5	13 +

For a proper use of the overshoes, it is important to ensure that the overshoes fit neatly over the user's footwear

Storage and maintenance



DRONIK ARBEITSSCHUTZ

Dronik Arbeitsschutz GmbH, Ubostr. 35, 81245 München
Tel: +49 89 8999 7500, Fax: +49 89 8999 7529
website: www.dronik-arbeitsschutz.de
email: info@dronik-arbeitsschutz.de